

NEW

From Solax

X-HYBRID

X1-HYBRID HV

X3-HYBRID HV



X1-Hybrid HV



X3-Hybrid HV

X1-HYBRID HV/ X3-HYBRID HV

The World's Leading Hybrid Inverter Just Got Better

More than just an inverter, the innovative X-Hybrid is an intelligent energy management system that stores surplus energy in batteries for later use.

The X-Hybrid works by storing surplus energy in batteries for later use, making it possible to utilize solar power time-independently by storing unused capacity. It converts and directs solar power to where it is needed, when it is needed. X-Hybrid is also supplied EPS (Emergency Power Supply) function, allowing the end-user to use their stored energy in the event of a power outage.

Get in touch now:

Global: +86 571-56260008

AU: +61 1300 476529

Website: www.solaxpower.com

DE: +49 7231 4180999

UK: +44 2476 586998

Email: info@solaxpower.com



X1-Hybrid HV (SINGLE PHASE)

X3-Hybrid HV (THREE PHASE)

X1-HYBRID-3.0T X1-HYBRID-3.7T X1-HYBRID-4.6T X1-HYBRID-5.0T X3-Hybrid-5.0T X3-Hybrid-6.0T X3-Hybrid-8.0T X3-Hybrid-10.0T

INPUT (DC)	X1-HYBRID-3.0T	X1-HYBRID-3.7T	X1-HYBRID-4.6T	X1-HYBRID-5.0T	X3-Hybrid-5.0T	X3-Hybrid-6.0T	X3-Hybrid-8.0T	X3-Hybrid-10.0T
Max.recommended DC power[W]	4000	5000	6000	6000	6000	8000	10000	13000
Max.DC voltage[V]	600	600	600	600	1000	1000	1000	1000
Nominal DC operating voltage[V]	360	360	360	360	720	720	720	720
Max.input current[A]	10/10	10/10	10/10	10/10	11/11	11/11	11/11	20/11
Max. short circuit current[A]	14/14	14/14	14/14	14/14	14/14	14/14	14/14	23/14
MPPT voltage range[V]	125-550	125-550	125-550	125-550	230-800	280-800	370-800	330-800
No. of MPP trackers	2	2	2	2	2	2	2	2
Strings per MPP tracker	1	1	1	1	1	1	1	2/1
OUTPUT AC								
Nominal AC power [VA]	3000	3680	4600	4999	5000	6000	8000	10000
Max. AC power [VA]	3000	3680	4600	4999	5000	6000	8000	10000
Rated grid voltage(AC voltage range) [V]	230(180 to 270)	230(180 to 270)	230(180 to 270)	230(180 to 270)	400(360 to 440)	400(360 to 440)	400(360 to 440)	400(360 to 440)
Rated grid frequency [Hz]	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60
Nominal AC current [A]	13	16	20	21.7	7.6	9	12.2	15
Max. AC current [A]	14.4	16	21	21.7	8.5	10	13.5	16
Displacement power factor	0.8 leading ... 0.8 lagging			0.8 leading ... 0.8 lagging				
Total harmonic distortion(THD, rated power) [%]	<2			<2				
Parallel operation	Yes			Yes				
Load control	Yes (optional)			Yes (optional)				
OUTPUT DC (BATTERY)								
Battery voltage range [V]	85-400			170-500				
Recommended battery voltage [V]	300			320				
Max.charging/discharging power [W]	6000			200		240	320	400
Max.charging/discharging current [A]	20			6000		8000	10000	10000
Communication interfaces	CAN/RS485			CAN/RS485				
Reverse connect protection	Yes			Yes				
EPS OUTPUT (WITH BATTERY)								
EPS rated power [VA]	4000	4000	5000	5000	5000	6000	8000	10000
EPS rated voltage [V], Frequency [Hz]	230, 50/60	230, 50/60	230, 50/60	230, 50/60	400/380, 50/60	400/380, 50/60	400/380, 50/60	400/380, 50/60
EPS rated current [A]	17.4	17.4	21.7	21.7	7.2	8.7	11.6	14.5
EPS peak power[W];Duration [s]	8000,10	8000,10	8000,10	8000,10	7500,60	9000,60	12000,60	14000,60
Switch time[s]	<0.5			<0.5				
Total harmonic distortion(THD, linear load) [%]	<2			<2				
Parallel operation	Being developed			Being developed				
EFFICIENCY								
MPPT efficiency [%]	99.90			99.90				
Euro efficiency [%]	97.00			97.00				
Max. efficiency [%]	97.80			97.80				
Battery charge/discharge efficiency [%]	96.5 (PV-BAT) 97.0 (BAT-AC)			97.8 (PV-BAT) 96.0 (BAT-AC)				
POWER CONSUMPTION								
Standby consumption(night) [W]	<7			<7				
Idle mode	YES			YES				
STANDARD								
Safety	IEC62109-1-2 / IEC62040			IEC62109-1-2 / IEC62040/ AS3100				
EMC	EN61000-6-1/EN61000-6-2/EN61000-6-3			EN61000-6-1/EN61000-6-2/EN61000-6-3				
Certification	VDE0126-1-1 A1:2012/VDE-AR-N4105/G83/G59/AS4777/EN50438/CEIO-21/VDE2510			VDE0126-1-1 A1:2012/VDE-AR-N4105/G59-3/AS4777/EN50438/CEI 0-21/IEC62040/IEC62619/ISO13849-2/SN29500/IEC615086				
ENVIRONMENT LIMIT								
Protection class	IP65			IP65				
Operating temperature range [°C]	-20 to+60 (derating at+45)			-25 to+60 (derating at+45)				
Altitude[m]	<2000			<2000				
Storage temperature[°C]	-20 to+60			-20 to+60				
Noise emission(typical) [dB]	<30			<30				
Over voltage category	III (electric supply side), II (PV side)			III (electric supply side), II (PV side)				
DIMENSION AND WEIGHT								
Dimensions(WxHxD) [mm]	482*464*182			456*655*228				
Weight[kg]	26.9			40				
Cooling concept	Natural			Natural				
Topology	Transformerless			Transformerless				
Communication	Ethernet, Meter, WIFI (optional), RF(optional), DRM, USB, ISO alarm, Parallel operation			Ethernet, Meter, WIFI (optional), RF(optional), DRM, USB, ISO alarm, Parallel operation				
LCD display	Backlight 20*4 character			Backlight 20*4 character				
Standard warranty [years]	5-10			5-10				

*Can be modified without notice.(V2)